

SECTION .0300 - OCEAN HAZARD AREAS

15A NCAC 07H .0301 OCEAN HAZARD CATEGORIES

The next broad grouping is composed of those AECs that are considered natural hazard areas along the Atlantic Ocean shoreline where, because of their special vulnerability to erosion or other adverse effects of sand, wind, and water, uncontrolled or incompatible development could unreasonably endanger life or property. Ocean hazard areas include beaches, frontal dunes, inlet lands, and other areas in which geologic, vegetative and soil conditions indicate a substantial possibility of excessive erosion or flood damage.

History Note: Authority G.S. 113A-107(a); 113A-107(b); 113A-113(b)(6a); 113A-113(b)(6b); 113A-113(b)(6d); 113A-124;
Eff. September 9, 1977.

15A NCAC 07H .0302 SIGNIFICANCE OF THE OCEAN HAZARD CATEGORY

(a) The primary causes of the hazards peculiar to the Atlantic shoreline are the constant forces exerted by waves, winds, and currents upon the unstable sands that form the shore. During storms, these forces are intensified and can cause significant changes in the bordering landforms and to structures located on them. Ocean hazard area property is in the ownership of a large number of private individuals as well as several public agencies and is used by a vast number of visitors to the coast. Ocean hazard areas are critical, therefore, because of both the severity of the hazards and the intensity of interest in the areas.

(b) The location and form of the various hazard area landforms, in particular the beaches, dunes, and inlets, are in a permanent state of flux, responding to meteorologically induced changes in the wave climate. For this reason, the appropriate location of structures on and near these landforms must be reviewed carefully in order to avoid their loss or damage. As a whole, the same flexible nature of these landforms which presents hazards to development situated immediately on them offers protection to the land, water, and structures located landward of them. The value of each landform lies in the particular role it plays in affording protection to life and property. (The role of each landform is described in detail in Technical Appendix 2 in terms of the physical processes most important to each.) Overall, however, the energy dissipation and sand storage capacities of the landforms are most essential for the maintenance of the landforms' protective function.

History Note: Authority G.S. 113A-107(a); 113A-107(b); 113A-113(b)(6a); 113A-113(b)(6b); 113A-113(b)(6d); 113A-124;
Eff. September 9, 1977;
Amended Eff. October 1, 1992.

15A NCAC 07H .0303 MANAGEMENT OBJECTIVE OF OCEAN HAZARD AREAS

(a) The CRC recognizes that absolute safety from the destructive forces indigenous to the Atlantic shoreline is an impossibility for development located adjacent to the coast. The loss of life and property to these forces, however, can be greatly reduced by the proper location and design of structures and by care taken in prevention of damage to natural protective features particularly primary and frontal dunes. Therefore, it is the CRC's objective to provide management policies and standards for ocean hazard areas that serve to eliminate unreasonable danger to life and property and achieve a balance between the financial, safety, and social factors that are involved in hazard area development.

(b) The purpose of these Rules shall be to further the goals set out in G.S. 113A-102(b), with particular attention to minimizing losses to life and property resulting from storms and long-term erosion, preventing encroachment of permanent structures on public beach areas, preserving the natural ecological conditions of the barrier dune and beach systems, and reducing the public costs of inappropriately sited development. Furthermore, it is the objective of the Coastal Resources Commission to protect present common-law and statutory public rights of access to and use of the lands and waters of the coastal area.

History Note: Authority G.S. 113A-107(b); 113A-113(b)(6) a.; 113A-113(b)(6) b.; 113A-113(b)(6)d.; 113A-124;
Eff. September 9, 1977;
Amended Eff. October 1, 1992; December 1, 1991; September 1, 1985; February 2, 1981.

15A NCAC 07H .0304 AECS WITHIN OCEAN HAZARD AREAS

The ocean hazard system of AECs contains all of the following areas:

- (1) Ocean Erodible Area. This is the area in which there exists a substantial possibility of excessive erosion and significant shoreline fluctuation. The seaward boundary of this area is the mean low water line. The landward extent of this area is determined as follows:
 - (a) a distance landward from the first line of stable natural vegetation to the recession line that would be established by multiplying the long-term annual erosion rate times 60, provided that, where there has been no long-term erosion or the rate is less than two feet per year, this distance shall be set at 120 feet landward from the first line of stable natural vegetation. For the purposes of this Rule, the erosion rates shall be the long-term average based on available historical data. The current long-term average erosion rate data for each segment of the North Carolina coast is depicted on maps entitled "Long Term Annual Shoreline Change Rates updated through 1998" and approved by the Coastal Resources Commission on January 29, 2004 (except as such rates may be varied in individual contested cases, declaratory or interpretive rulings). The maps are available without cost from any local permit officer or the Division of Coastal Management; and
 - (b) a distance landward from the recession line established in Sub-Item (1)(a) of this Rule to the recession line that would be generated by a storm having a one percent chance of being equaled or exceeded in any given year.
- (2) The High Hazard Flood Area. This is the area subject to high velocity waters including hurricane wave wash) in a storm having a one percent chance of being equaled or exceeded in any given year, as identified as zone V1-30 on the flood insurance rate maps of the Federal Insurance Administration, U.S. Department of Housing and Urban Development.
- (3) Inlet Hazard Area. The inlet hazard areas are natural-hazard areas that are especially vulnerable to erosion, flooding and other adverse effects of sand, wind, and water because of their proximity to dynamic ocean inlets. This area shall extend landward from the normal low water line a distance sufficient to encompass that area within which the inlet shall, based on statistical analysis, migrate, and shall consider such factors as previous inlet territory, structurally weak areas near the inlet and external influences such as jetties and channelization. The areas identified as suggested Inlet Hazard Areas included in the report entitled INLET HAZARD AREAS, The Final Report and Recommendations to the Coastal Resources Commission, 1978, as amended in 1981, by Loie J. Priddy and Rick Carraway are incorporated by reference without future changes are hereby designated as Inlet Hazard Areas except that the Cape Fear Inlet Hazard Area as shown on said map shall not extend northeast of the Baldhead Island marina entrance channel. In all cases, this area shall be an extension of the adjacent ocean erodible area and in no case shall the width of the inlet hazard area be less than the width of the adjacent ocean erodible area. This report is available for inspection at the Department of Environment and Natural Resources, Division of Coastal Management, 400 Commerce Avenue, Morehead City, North Carolina. Small scaled photo copies are available at no charge.
- (4) Unvegetated Beach Area. Beach areas within the Ocean Hazard Area where no stable natural vegetation is present may be designated as an unvegetated beach area on either a permanent or temporary basis:
 - (a) An area appropriate for permanent designation as an unvegetated beach area is a dynamic area that is subject to rapid unpredictable landform change from wind and wave action. The areas in this category shall be designated following detailed studies by the Coastal Resources Commission. These areas shall be designated on maps approved by the Commission and available without cost from any local permit officer or the Division of Coastal Management.
 - (b) An area that is suddenly unvegetated as a result of a hurricane or other major storm event may be designated as an unvegetated beach area for a specific period of time. At the expiration of the time specified by the Commission, the area shall return to its pre-storm designation. Areas appropriate for such designation are those in which vegetation has been lost over such a large land area that extrapolation of the vegetation line under the procedure set out in Rule .0305(e) of this Section is inappropriate.

The Commission designates as temporary unvegetated beach areas those oceanfront areas on Hatteras Island west of the new inlet breach in Dare County in which the vegetation line as shown on Dare County orthophotographs dated 4 February 2002 through 10 February 2002 was destroyed as a result of Hurricane Isabel on September 18, 2003 and the remnants of which were subsequently buried by the construction of an emergency berm. This designation shall continue until such time as stable, natural vegetation has reestablished or until the area is permanently designated as an unvegetated beach area pursuant to Sub-Item 4(a) of this Rule.

History Note: Authority G.S. 113A-107; 113A-113; 113A-124; Eff. September 9, 1977; Amended Eff. December 1, 1993; November 1, 1988; September 1, 1986; December 1, 1985; Temporary Amendment Eff. October 10, 1996; Amended Eff. April 1, 1997; Temporary Amendment Eff. October 10, 1996 Expired on July 29, 1997;

15A NCAC 7H .0305 GENERAL IDENTIFICATION AND DESCRIPTION OF LANDFORMS

(a) This section describes natural and man-made features that are found within the ocean hazard area of environmental concern.

- (1) Ocean Beaches. Ocean beaches are lands consisting of unconsolidated soil materials that extend from the mean low water line landward to a point where either:
 - (A) the growth of vegetation occurs, or
 - (B) a distinct change in slope or elevation alters the configuration of the landform, whichever is farther landward.
- (2) Nearshore. The nearshore is the portion of the beach seaward of mean low water that is characterized by dynamic changes both in space and time as a result of storms.
- (3) Primary Dunes. Primary dunes are the first mounds of sand located landward of the ocean beaches having an elevation equal to the mean flood level (in a storm having a one percent chance of being equaled or exceeded in any given year) for the area plus six feet. The primary dune extends landward to the lowest elevation in the depression behind that same mound of sand (commonly referred to as the dune trough).
- (4) Frontal Dunes. The frontal dune is deemed to be the first mound of sand located landward of the ocean beach having sufficient vegetation, height, continuity and configuration to offer protective value.
- (5) Vegetation Line. The vegetation line refers to the first line of stable and natural vegetation, which shall be used as the reference point for measuring oceanfront setbacks. This line represents the boundary between the normal dry-sand beach, which is subject to constant flux due to waves, tides, storms and wind, and the more stable upland areas. The vegetation line is generally located at or immediately oceanward of the seaward toe of the frontal dune or erosion escarpment. The Division of Coastal Management or Local Permit Officer shall determine the location of the stable and natural vegetation line based on visual observations of plant composition and density. If the vegetation has been planted, it may be considered stable when the majority of the plant stems are from continuous rhizomes rather than planted individual rooted sets. The vegetation may be considered natural when the majority of the plants are mature and additional species native to the region have been recruited, providing stem and rhizome densities that are similar to adjacent areas that are naturally occurring. In areas where there is no stable natural vegetation present, this line may be established by interpolation between the nearest adjacent stable natural vegetation by on ground observations or by aerial photographic interpretation.
- (6) Static Vegetation Line. In areas within the boundaries of a large-scale beach fill project, the vegetation line that existed within one year prior to the onset of initial project construction shall be defined as the static vegetation line. A static vegetation line shall be established in coordination with the Division of Coastal Management using on-ground observation and survey or aerial imagery for all areas of oceanfront that undergo a large-scale beach fill project. Once a static vegetation line is established, and after the onset of project construction, this line shall be used as the reference point for measuring oceanfront setbacks in all locations where it is landward of the vegetation line. In all locations where the vegetation line as defined in this Rule is landward of the static vegetation line, the vegetation line shall be used as the reference point for measuring oceanfront setbacks. A static vegetation line shall not be established where a static vegetation line is already in place, including those established by the Division of Coastal Management prior to the effective date of this Rule. A record of all static vegetation lines, including those established by the Division of Coastal Management prior to the effective date of this Rule, shall be maintained by the Division of Coastal Management for determining development standards as set forth in Rule .0306 of this Section. Because the impact of Hurricane Floyd (September 1999) caused significant portions of the vegetation line in the Town of Oak Island and the Town of Ocean Isle Beach to be relocated landward of its pre-storm position, the static line for areas landward of the beach fill construction in the Town of Oak Island and the Town of Ocean Isle Beach, the onset of which occurred in 2000, shall be defined by the general trend of the vegetation line established by the Division of Coastal Management from June 1998 aerial orthophotography.
- (7) Beach Fill. Beach fill refers to the placement of sediment along the oceanfront shoreline. Sediment used solely to establish or strengthen dunes shall not be considered a beach fill project under this Rule. A large-scale beach fill project shall be defined as any volume of sediment greater than 300,000 cubic yards or any storm protection project constructed by the U.S. Army Corps of Engineers. The onset of construction shall be defined as the date sediment placement begins with the exception of projects completed prior to the effective date of this Rule, in which case the award of contract date will be considered the onset of construction.
- (8) Erosion Escarpment. The normal vertical drop in the beach profile caused from high tide or storm tide erosion.

- (9) Measurement Line. The line from which the ocean hazard setback as described in Rule .0306(a) of this Section is measured in the unvegetated beach area of environmental concern as described in Rule .0304(4) of this Section. Procedures for determining the measurement line in areas designated pursuant to Rule .0304(4)(a) of this Section shall be adopted by the Commission for each area where such a line is designated pursuant to the provisions of G.S. 150B. These procedures shall be available from any local permit officer or the Division of Coastal Management. In areas designated pursuant to Rule .0304(4)(b) of this Section, the Division of Coastal Management shall establish a measurement line that approximates the location at which the vegetation line is expected to reestablish by:

- (A) determining the distance the vegetation line receded at the closest vegetated site to the proposed development site; and
- (B) locating the line of stable natural vegetation on the most current pre-storm aerial photography of the proposed development site and moving this line landward the distance determined in Subparagraph (g)(1) of this Rule.

The measurement line established pursuant to this process shall in every case be located landward of the average width of the beach as determined from the most current pre-storm aerial photography.

(b) For the purpose of public and administrative notice and convenience, each designated minor development permit-letting agency with ocean hazard areas may designate, subject to CRC approval in accordance with the local implementation and enforcement plan as defined 15A NCAC 07I .0500, a readily identifiable land area within which the ocean hazard areas occur.

This designated notice area must include all of the land areas defined in Rule .0304 of this Section. Natural or man-made landmarks may be considered in delineating this area.

History Note: Authority G.S. 113A-107; 113A-113(b)(6); 113A-124; Eff. September 9, 1977; Amended Eff. December 1, 1992; September 1, 1986; December 1, 1985; February 2, 1981; Temporary Amendment Eff. October 10, 1996; Amended Eff. January 1, 1997; Temporary Amendment Eff. October 10, 1996 Expired on July 29, 1997; Temporary Amendment Eff. October 22, 1997; Amended Eff. April 1, 2008; August 1, 2002; August 1, 1998

15A NCAC 07H .0306 GENERAL USE STANDARDS FOR OCEAN HAZARD AREAS

(a) In order to protect life and property, all development not otherwise specifically exempted or allowed by law or elsewhere in the CRC's Rules shall be located according to whichever of the following is applicable:

- (1) The ocean hazard setback for development is measured in a landward direction from the vegetation line, the static vegetation line or the measurement line, whichever is applicable. The setback distance is determined by both the size of development and the shoreline erosion rate as defined in 15A NCAC 07H .0304. Development size is defined by total floor area for structures and buildings or total area of footprint for development other than structures and buildings. Total floor area includes the following:
 - (A) The total square footage of heated or air-conditioned living space;
 - (B) The total square footage of parking elevated above ground level; and
 - (C) The total square footage of non-heated or non-air-conditioned areas elevated above ground level, excluding attic space that is not designed to be load bearing;
Decks, roof-covered porches and walkways are not included in the total floor area unless they are enclosed with material other than screen mesh or are being converted into an enclosed space with material other than screen mesh.
- (2) With the exception of those types of development defined in 15A NCAC 07H .0309, no development, including any portion of a building or structure, shall extend oceanward of the ocean hazard setback distance. This includes roof overhangs and elevated structural components that are cantilevered, knee braced, or otherwise extended beyond the support of pilings or footings. The ocean hazard setback is established based on the following criteria:
 - (A) A building or other structure less than 5,000 square feet requires a minimum setback of 60 feet or 30 times the shoreline erosion rate, whichever is greater;
 - (B) A building or other structure greater than or equal to 5,000 square feet but less than 10,000 square feet requires a minimum setback of 120 feet or 60 times the shoreline erosion rate, whichever is greater;
 - (C) A building or other structure greater than or equal to 10,000 square feet but less than 20,000 square feet requires a minimum setback of 130 feet or 65 times the shoreline erosion rate, whichever is greater;
 - (D) A building or other structure greater than or equal to 20,000 square feet but less than 40,000 square feet requires a minimum setback of 140 feet or 70 times the shoreline erosion rate, whichever is greater;
 - (E) A building or other structure greater than or equal to 40,000 square feet but less than 60,000 square feet requires a minimum setback of 150 feet or 75 times the shoreline erosion rate, whichever is greater;
 - (F) A building or other structure greater than or equal to 60,000 square feet but less than 80,000 square feet

- (G) requires a minimum setback of 160 feet or 80 times the shoreline erosion rate, whichever is greater;
- (H) A building or other structure greater than or equal to 80,000 square feet but less than 100,000 square feet requires a minimum setback of 170 feet or 85 times the shoreline erosion rate, whichever is greater;
- (I) A building or other structure greater than or equal to 100,000 square feet requires a minimum setback of 180 feet or 90 times the shoreline erosion rate, whichever is greater;
- (J) Infrastructure that is linear in nature such as roads, bridges, pedestrian access such as boardwalks and sidewalks, and utilities providing for the transmission of electricity, water, telephone, cable television, data, storm water and sewer requires a minimum setback of 60 feet or 30 times the shoreline erosion rate, whichever is greater;
- (K) Parking lots greater than or equal to 5,000 square feet requires a setback of 120 feet or 60 times the shoreline erosion rate, whichever is greater; and
- (K) Notwithstanding any other setback requirement of this Subparagraph, a building or other structure greater than or equal to 5,000 square feet in a community with a static line exception in accordance with 15A NCAC 07J .1200 requires a minimum setback of 120 feet or 60 times the shoreline erosion rate in place at the time of permit issuance, whichever is greater. The setback shall be measured landward from either the static_vegetation line, the vegetation line or measurement line, whichever is farthest landward.

(3) If a primary dune exists in the AEC on or landward of the lot on which the development is proposed, the development shall be landward of the crest of the primary dune or the ocean hazard_setback, whichever is farthest from vegetation line, static vegetation line or measurement line, whichever is applicable. For existing lots, however, where setting the development landward of the crest of the primary dune would preclude any practical use of the lot, development may be located oceanward of the primary dune. In such cases, the development may be located landward of the ocean hazard setback but shall not be located on or oceanward of a frontal dune. The words "existing lots" in this Rule shall mean a lot or tract of land which, as of June 1, 1979, is specifically described in a recorded plat and which cannot be enlarged by combining the lot or tract of land with a contiguous lot(s) or tract(s) of land under the same ownership.

(4) If no primary dune exists, but a frontal dune does exist in the AEC on or landward of the lot on which the development is proposed, the development shall be set landward of the frontal dune or landward of the ocean hazard setback whichever is farthest from the vegetation line, static_vegetation line or measurement line, whichever is applicable.

(5) If neither a primary nor frontal dune exist in the AEC on or landward of the lot on which development is proposed, the structure shall be landward of the ocean hazard setback.

(6) Structural additions or increases in the footprint or total floor area of a building or structure represent expansions to the total floor area and shall meet the setback requirements established in this Rule and 15A NCAC 07H .0309(a). New development landward of the applicable setback may be cosmetically, but shall not be structurally, attached to an existing structure that does not conform with current setback requirements.

(7) Established common-law and statutory public rights of access to and use of public trust lands and waters in ocean hazard areas shall not be eliminated or restricted. Development shall not encroach upon public accessways nor shall it limit the intended use of the accessways.

(8) Beach fill as defined in this Section represents a temporary response to coastal erosion, and compatible beach fill as defined in 15A NCAC 07H .0312 can be expected to erode at least as fast as, if not faster than, the pre-project beach. Furthermore, there is no assurance of future funding or beach-compatible sediment for continued beach fill projects and project maintenance. A vegetation line that becomes established oceanward of the pre-project vegetation line in an area that has received beach fill may be more vulnerable to natural hazards along the oceanfront. A development setback measured from the vegetation line provides less protection from ocean hazards. Therefore, development setbacks in areas that have received large-scale beach fill as defined in 15A NCAC 07H .0305 shall be measured landward from the static vegetation line as defined in this Section. However, in order to allow for development landward of the large-scale beach fill project that is less than 2,500 square feet and cannot meet the setback requirements from the static vegetation line, but can or has the potential to meet the setback requirements from the vegetation line set forth in Subparagraph (1) and (2)(A) of this Paragraph a local government or community may petition the Coastal Resources Commission for a "static line exception" in accordance with 15A NCAC 07J .1200 to allow development of property that lies both within the jurisdictional boundary of the petitioner as well as the boundaries of the large-scale beach fill project. This static line exception shall also allow development greater than 5,000 square feet to use the setback provisions defined in Part (a)(2)(K) of this Rule in areas that lie within the jurisdictional boundary of the petitioner as well as the boundaries of the large-scale beach fill project. The procedures for a static line exception request are defined in 15A NCAC 07J .1200. If the request is approved, the Coastal Resources Commission shall allow development setbacks to be measured from a vegetation line that is oceanward of the static vegetation line under the following conditions:

- (A) Development meets all setback requirements from the vegetation line defined in Subparagraphs (a)(1) and (a)(2)(A) of this Rule;
- (B) Total floor area of a building is no greater than 2,500 square feet;

- (C) Development setbacks are calculated from the shoreline erosion rate in place at the time of permit issuance;
- (D) No portion of a building or structure, including roof overhangs and elevated portions that are cantilevered, knee braced or otherwise extended beyond the support of pilings or footings, extends oceanward of the landward-most adjacent building or structure. When the configuration of a lot precludes the placement of a building or structure in line with the landward-most adjacent building or structure, an average line of construction shall be determined by the Division of Coastal Management on a case-by-case basis in order to determine an ocean hazard setback that is landward of the vegetation line, a distance no less than 30 times the shoreline erosion rate or 60 feet, whichever is greater;
- (E) With the exception of swimming pools, the development defined in 15A NCAC 07H .0309(a) is allowed oceanward of the static vegetation line; and
- (F) Development is not eligible for the exception defined in 15A NCAC 07H .0309(b).

(b) In order to avoid weakening the protective nature of ocean beaches and primary and frontal dunes, no development is permitted that involves the removal or relocation of primary or frontal dune sand or vegetation thereon which would adversely affect the integrity of the dune. Other dunes within the ocean hazard area shall not be disturbed unless the development of the property is otherwise impracticable, and any disturbance of any other dunes is allowed only to the extent allowed by 15A NCAC 07H .0308(b).

(c) Development shall not cause irreversible damage to historic architectural or archaeological resources documented by the Division of Archives and History, the National Historical Registry, the local land-use plan, or other sources.

(d) Development shall comply with minimum lot size and set back requirements established by local regulations.

(e) Mobile homes shall not be placed within the high hazard flood area unless they are within mobile home parks existing as of June 1, 1979.

(f) Development shall comply with general management objective for ocean hazard areas set forth in 15A NCAC 07H .0303.

(g) Development shall not interfere with legal access to, or use of, public resources nor shall such development increase the risk of damage to public trust areas.

(h) Development proposals shall incorporate measures to avoid or minimize adverse impacts of the project. These measures shall be implemented at the applicant's expense and may include actions that:

- (1) minimize or avoid adverse impacts by limiting the magnitude or degree of the action,
- (2) restore the affected environment, or
- (3) compensate for the adverse impacts by replacing or providing substitute resources.

(i) Prior to the issuance of any permit for development in the ocean hazard AECs, there shall be a written acknowledgment from the applicant to DCM that the applicant is aware of the risks associated with development in this hazardous area and the limited suitability of this area for permanent structures. By granting permits, the Coastal Resources Commission does not guarantee the safety of the development and assumes no liability for future damage to the development.

(j) All relocation of structures requires permit approval. Structures relocated with public funds shall comply with the applicable setback line as well as other applicable AEC rules. Structures including septic tanks and other essential accessories relocated entirely with non-public funds shall be relocated the maximum feasible distance landward of the present location; septic tanks may not be located oceanward of the primary structure. In these cases, all other applicable local and state rules shall be met.

(k) Permits shall include the condition that any structure shall be relocated or dismantled when it becomes imminently threatened by changes in shoreline configuration as defined in 15A NCAC 07H .0308(a)(2)(B). The structure(s) shall be relocated or dismantled within two years of the time when it becomes imminently threatened, and in any case upon its collapse or subsidence. However, if natural shoreline recovery or beach renourishment takes place within two years of the time the structure becomes imminently threatened, so that the structure is no longer imminently threatened, then it need not be relocated or dismantled at that time. This condition shall not affect the permit holder's right to seek authorization of temporary protective measures allowed under 15A NCAC 07H .0308(a)(2).

History Note: Authority G.S. 113A-107; 113A-113(b)(6); 113A-124; Eff. September 9, 1977; Amended Eff. December 1, 1991; March 1, 1988; September 1, 1986; December 1, 1985; RRC Objection due to ambiguity Eff. January 24, 1992; Amended Eff. March 1, 1992; RRC Objection due to ambiguity Eff. May 21, 1992; Amended Eff. February 1, 1993; October 1, 1992; June 19, 1992; RRC Objection due to ambiguity Eff. May 18, 1995; Amended Eff. August 11, 2009; April 1, 2007; November 1, 2004; June 27, 1995.

*History Note: Authority G.S. 113A-107(a); 113A-107(b); 113A-113(b)(6)a; 113A-113(b)(6)b; 113A-113(b)(6)d;
Eff. September 9, 1977;
Amended Eff. January 24, 1978;
Repealed Eff. September 15, 1979.*

15A NCAC 07H .0308 SPECIFIC USE STANDARDS FOR OCEAN HAZARD AREAS

(a) Ocean Shoreline Erosion Control Activities:

- (1) Use Standards Applicable to all Erosion Control Activities:
 - (A) All oceanfront erosion response activities shall be consistent with the general policy statements in 15A NCAC 07M .0200.
 - (B) Permanent erosion control structures may cause significant adverse impacts on the value and enjoyment of adjacent properties or public access to and use of the ocean beach, and, therefore, are prohibited. Such structures include bulkheads, seawalls, revetments, jetties, groins and breakwaters.
 - (C) Rules concerning the use of oceanfront erosion response measures apply to all oceanfront properties without regard to the size of the structure on the property or the date of its construction.
 - (D) All permitted oceanfront erosion response projects, other than beach bulldozing and temporary placement of sandbag structures, shall demonstrate sound engineering for their planned purpose.
 - (E) Shoreline erosion response projects shall not be constructed in beach or estuarine areas that sustain substantial habitat for fish and wildlife species, as identified by natural resource agencies during project review, unless mitigation measures are incorporated into project design, as set forth in Rule .0306(i) of this Section.
 - (F) Project construction shall be timed to minimize adverse effects on biological activity.
 - (G) Prior to completing any erosion response project, all exposed remnants of or debris from failed erosion control structures must be removed by the permittee.
 - (H) Erosion control structures that would otherwise be prohibited by these standards may be permitted on finding that:
 - (i) the erosion control structure is necessary to protect a bridge which provides the only existing road access on a barrier island, that is vital to public safety, and is imminently threatened by erosion as defined in provision (a)(2)(B) of this subchapter;
 - (ii) the erosion response measures of relocation, beach nourishment or temporary stabilization are not adequate to protect public health and safety; and
 - (iii) the proposed erosion control structure will have no adverse impacts on adjacent properties in private ownership or on public use of the beach.
 - (I) Structures that would otherwise be prohibited by these standards may also be permitted on finding that:
 - (i) the structure is necessary to protect a state or federally registered historic site that is imminently threatened by shoreline erosion as defined in provision (a)(2)(B) of this subchapter; and
 - (ii) the erosion response measures of relocation, beach nourishment or temporary stabilization are not adequate and practicable to protect the site; and
 - (iii) the structure is limited in extent and scope to that necessary to protect the site; and
 - (iv) any permit for a structure under this Part (I) may be issued only to a sponsoring public agency for projects where the public benefits outweigh the short or long range adverse impacts. Additionally, the permit shall include conditions providing for mitigation or minimization by that agency of any unavoidable adverse impacts on adjoining properties and on public access to and use of the beach.
 - (J) Structures that would otherwise be prohibited by these standards may also be permitted on finding that:
 - (i) the structure is necessary to maintain an existing commercial navigation channel of regional significance within federally authorized limits; and
 - (ii) dredging alone is not practicable to maintain safe access to the affected channel; and
 - (iii) the structure is limited in extent and scope to that necessary to maintain the channel; and
 - (iv) the structure shall not adversely impact fisheries or other public trust resources; and
 - (v) any permit for a structure under this Part (J) may be issued only to a sponsoring public agency for projects where the public benefits outweigh the short or long range adverse impacts. Additionally, the permit shall include conditions providing for mitigation or minimization by that agency of any unavoidable adverse impacts on adjoining properties and on public access to and use of the beach.

- (K) The Commission may renew a permit for an erosion control structure issued pursuant to a variance granted by the Commission prior to 1 July 1995. The Commission may authorize the replacement of a permanent erosion control structure that was permitted by the Commission pursuant to a variance granted by the Commission prior to 1 July 1995 if the Commission finds that:
 - (i) the structure will not be enlarged beyond the dimensions set out in the permit;
 - (ii) there is no practical alternative to replacing the structure that will provide the same or similar benefits; and
 - (iii) the replacement structure will comply with all applicable laws and with all rules, other than the rule or rules with respect to which the Commission granted the variance, that are in effect at the time the structure is replaced.
 - (L) Proposed erosion response measures using innovative technology or design shall be considered as experimental and shall be evaluated on a case-by-case basis to determine consistency with 15A NCAC 7M .0200 and general and specific use standards within this Section.
- (2) Temporary Erosion Control Structures:
- (A) Permittable temporary erosion control structures shall be limited to sandbags placed landward of mean high water and parallel to the shore.
 - (B) Temporary erosion control structures as defined in Part (2)(A) of this Subparagraph shall be used to protect only imminently threatened roads and associated right of ways, and buildings and their associated septic systems. A structure shall be considered imminently threatened if its foundation, septic system, or right-of-way in the case of roads, is less than 20 feet away from the erosion scarp. Buildings and roads located more than 20 feet from the erosion scarp or in areas where there is no obvious erosion scarp may also be found to be imminently threatened when site conditions, such as a flat beach profile or accelerated erosion, increase the risk of imminent damage to the structure.
 - (C) Temporary erosion control structures shall be used to protect only the principal structure and its associated septic system, but not appurtenances such as pools, gazebos, decks or any amenity that is allowed as an exception to the erosion setback requirement.
 - (D) Temporary erosion control structures may be placed seaward of a septic system when there is no alternative to relocate it on the same or adjoining lot so that it is landward of or in line with the structure being protected.
 - (E) Temporary erosion control structures shall not extend more than 20 feet past the sides of the structure to be protected. The landward side of such temporary erosion control structures shall not be located more than 20 feet seaward of the structure to be protected or the right-of-way in the case of roads. If a building or road is found to be imminently threatened and at an increased risk of imminent damage due to site conditions such as a flat beach profile or accelerated erosion, temporary erosion control structures may be located more than 20 feet seaward of the structure being protected. In cases of increased risk of imminent damage, the location of the temporary erosion control structures shall be determined by the Director of the Division of Coastal Management or their designee.
 - (F) Temporary erosion control structures may remain in place for up to two years after the date of approval if they are protecting a building with a total floor area of 5000 sq. ft. or less and its associated septic system, or, for up to five years for a building with a total floor area of more than 5000 sq. ft. and its associated septic system. Temporary erosion control structures may remain in place for up to five years if they are protecting a bridge or a road. The property owner shall be responsible for removal of the temporary structure within 30 days of the end of the allowable time period.
 - (G) Temporary sandbag erosion control structures may remain in place for up to five years from the date of approval if they are located in a community that is actively pursuing a beach nourishment project, and for up to eight years from the date of approval if they are located in an Inlet Hazard Area adjacent to an inlet for which a community is actively pursuing an inlet relocation project. For purposes of this Rule, a community is considered to be actively pursuing a beach nourishment or inlet relocation project if it has:
 - (i) an active CAMA permit, where necessary, approving such project; or
 - (ii) been identified by a U.S. Army Corps of Engineers' Beach Nourishment Reconnaissance Study, General Reevaluation Report, Coastal Storm Damage Reduction Study or an ongoing feasibility study by the U.S. Army Corps of Engineers and a commitment of local or federal money, when necessary; or
 - (iii) received a favorable economic evaluation report on a federal project or,
 - (iv) is in the planning stages of a project that has been designed by the U.S. Army Corps of Engineers or persons meeting applicable State occupational licensing requirements and

has been initiated by a local government or community with a commitment of local or state funds to construct the project and the identification of the financial resources or funding bases necessary to fund the beach nourishment or inlet relocation project.

If beach nourishment or inlet relocation is rejected by the sponsoring agency or community, or ceases to be actively planned for a section of shoreline, the time extension is void for that section of beach or community and existing sandbags are subject to all applicable time limits set forth in Part (F) of this Subparagraph.

- (H) Once the temporary erosion control structure is determined to be unnecessary due to relocation or removal of the threatened structure, a storm protection project constructed by the U.S. Army Corps of Engineers, a large-scale beach nourishment project or an inlet relocation project, it shall be removed by the property owner within 30 days of official notification from the Division of Coastal Management regardless of the time limit placed on the temporary erosion control structure.
 - (I) Removal of temporary erosion control structures shall not be required if they are covered by dunes with stable and natural vegetation.
 - (J) The property owner shall be responsible for the removal of remnants of all portions of any damaged temporary erosion control structure.
 - (K) Sandbags used to construct temporary erosion control structures shall be tan in color and three to five feet wide and seven to 15 feet long when measured flat. Base width of the structure shall not exceed 20 feet, and the height shall not exceed six feet.
 - (L) Soldier pilings and other types of devices to anchor sandbags shall not be allowed.
 - (M) An imminently threatened structure may be protected only once, regardless of ownership unless the threatened structure is located in an Inlet Hazard Area and in a community that is actively pursuing an inlet relocation project in accordance with (G) of this Subparagraph. Existing temporary erosion control structures located in Inlet Hazard Areas may be eligible for an additional eight year permit extension provided that the structure being protected is still imminently threatened, the temporary erosion control structure is in compliance with requirements of this Subchapter and the community in which it is located is actively pursuing an inlet relocation project in accordance with Part (G) of this Subparagraph. In the case of a building, a temporary erosion control structure may be extended, or new segments constructed, if additional areas of the building become imminently threatened. Where temporary structures are installed or extended incrementally, the time period for removal under Part (F) or (G) of this Subparagraph shall begin at the time the initial erosion control structure is installed. For the purpose of this Rule:
 - (i) a building and septic system shall be considered as separate structures.
 - (ii) a road or highway shall be allowed to be incrementally protected as sections become imminently threatened. The time period for removal of each section of sandbags shall begin at the time that section is installed in accordance with Part (F) or (G) of this Subparagraph.
 - (N) Existing sandbag structures may be repaired or replaced within their originally permitted dimensions during the time period allowed under Part (F) or (G) of this Subparagraph.
- (3) Beach Nourishment. Sand used for beach nourishment shall be compatible with existing grain size and type. Sand to be used for beach nourishment shall be taken only from those areas where the resulting environmental impacts will be minimal.
- (4) Beach Bulldozing. Beach bulldozing (defined as the process of moving natural beach material from any point seaward of the first line of stable vegetation to create a protective sand dike or to obtain material for any other purpose) is development and may be permitted as an erosion response if the following conditions are met:
- (A) The area on which this activity is being performed shall maintain a slope of adequate grade so as to not endanger the public or the public's use of the beach and shall follow the pre-emergency slope as closely as possible. The movement of material utilizing a bulldozer, front end loader, backhoe, scraper, or any type of earth moving or construction equipment shall not exceed one foot in depth measured from the pre-activity surface elevation;
 - (B) The activity shall not exceed the lateral bounds of the applicant's property unless he has permission of the adjoining land owner(s);
 - (C) Movement of material from seaward of the mean low water line will require a CAMA Major Development and State Dredge and Fill Permit;
 - (D) The activity shall not increase erosion on neighboring properties and shall not have an adverse effect on natural or cultural resources;
 - (E) The activity may be undertaken to protect threatened on-site waste disposal systems as well as the threatened structure's foundations.

(b) Dune Establishment and Stabilization. Activities to establish dunes shall be allowed so long as the following conditions are met:

- (1) Any new dunes established shall be aligned to the greatest extent possible with existing adjacent dune ridges and shall be of the same general configuration as adjacent natural dunes.
- (2) Existing primary and frontal dunes shall not, except for beach nourishment and emergency situations, be broadened or extended in an oceanward direction.
- (3) Adding to dunes shall be accomplished in such a manner that the damage to existing vegetation is minimized. The filled areas shall be immediately replanted or temporarily stabilized until planting can be successfully completed.
- (4) Sand used to establish or strengthen dunes shall be of the same general characteristics as the sand in the area in which it is to be placed.
- (5) No new dunes shall be created in inlet hazard areas.
- (6) Sand held in storage in any dune, other than the frontal or primary dune, may be redistributed within the AEC provided that it is not placed any farther oceanward than the crest of a primary dune or landward toe of a frontal dune.
- (7) No disturbance of a dune area shall be allowed when other techniques of construction can be utilized and alternative site locations exist to avoid unnecessary dune impacts.

(c) Structural Accessways:

- (1) Structural accessways shall be permitted across primary dunes so long as they are designed and constructed in a manner that entails negligible alteration on the primary dune. Structural accessways shall not be considered threatened structures for the purpose of Paragraph (a) of this Rule.
- (2) An accessway shall be conclusively presumed to entail negligible alteration of a primary dune provided that:
 - (A) The accessway is exclusively for pedestrian use;
 - (B) The accessway is less than six feet in width;
 - (C) The accessway is raised on posts or pilings of five feet or less depth, so that wherever possible only the posts or pilings touch the frontal dune. Where this is deemed impossible, the structure shall touch the dune only to the extent absolutely necessary. In no case shall an accessway be permitted if it will diminish the dune's capacity as a protective barrier against flooding and erosion; and
 - (D) Any areas of vegetation that are disturbed are revegetated as soon as feasible.
- (3) An accessway which does not meet Part (2)(A) and (B) of this Paragraph shall be permitted only if it meets a public purpose or need which cannot otherwise be met and it meets Part (2)(C) of this Paragraph. Public fishing piers shall not be deemed to be prohibited by this Rule, provided all other applicable standards are met.
- (4) In order to avoid weakening the protective nature of primary and frontal dunes a structural accessway (such as a "Hatteras ramp") shall be provided for any off-road vehicle (ORV) or emergency vehicle access. Such accessways shall be no greater than 10 feet in width and shall be constructed of wooden sections fastened together over the length of the affected dune area.

(d) Building Construction Standards. New building construction and any construction identified in .0306(a)(5) and 07J .0210 shall comply with the following standards:

- (1) In order to avoid danger to life and property, all development shall be designed and placed so as to minimize damage due to fluctuations in ground elevation and wave action in a 100-year storm. Any building constructed within the ocean hazard area shall comply with relevant sections of the North Carolina Building Code including the Coastal and Flood Plain Construction Standards and the local flood damage prevention ordinance as required by the National Flood Insurance Program. If any provision of the building code or a flood damage prevention ordinance is inconsistent with any of the following AEC standards, the more restrictive provision shall control.
- (2) All building in the ocean hazard area shall be on pilings not less than eight inches in diameter if round or eight inches to a side if square.
- (3) All pilings shall have a tip penetration greater than eight feet below the lowest ground elevation under the structure. For those structures so located on or seaward of the primary dune, the pilings shall extend to five feet below mean sea level.
- (4) All foundations shall be adequately designed to be stable during applicable fluctuations in ground elevation and wave forces during a 100-year storm. Cantilevered decks and walkways shall meet this standard or shall be designed to break-away without structural damage to the main structure.

History Note: Authority G.S. 113A-107(a); 113A-107(b); 113A-113(b)(6)a.,b.,d.; 113A-124; Eff. June 1, 1979; Filed as a Temporary Amendment Eff. June 20, 1989, for a period of 180 days to expire on December 17, 1989;

Amended Eff. August 3, 1992; December 1, 1991; March 1, 1990; December 1, 1989;
RRC Objection Eff. November 19, 1992 due to ambiguity;
RRC Objection Eff. January 21, 1993 due to ambiguity;
Amended Eff. March 1, 1993; December 28, 1992;
RRC Objection Eff. March 16, 1995 due to ambiguity;
Amended Eff. April 1, 1999; February 1, 1996; May 4, 1995;
Temporary Amendment Eff. July 3, 2000; May 22, 2000;
Amended Eff. July 1, 2009; April 1, 2008; February 1, 2006; August 1, 2002.

15A NCAC 07H .0309 USE STANDARDS FOR OCEAN HAZARD AREAS: EXCEPTIONS

(a) The following types of development shall be permitted seaward of the oceanfront setback requirements of Rule .0306(a) of the Subchapter if all other provisions of this Subchapter and other state and local regulations are met:

- (1) campsites;
- (2) parking areas with clay, packed sand or gravel;
- (3) elevated decks not exceeding a footprint of 500 square feet;
- (4) beach accessways consistent with Rule .0308(c) of this Subchapter;
- (5) unenclosed, uninhabitable gazebos with a footprint of 200 square feet or less;
- (6) uninhabitable, single-story storage sheds with a foundation or floor consisting of wood, clay, packed sand or gravel, and a footprint of 200 square feet or less;
- (7) temporary amusement stands;
- (8) sand fences; and
- (9) swimming pools.

In all cases, this development shall be permitted only if it is landward of the vegetation line; involves no alteration or removal of primary or frontal dunes which would compromise the integrity of the dune as a protective landform or the dune vegetation; has overwalks to protect any existing dunes; is not essential to the continued existence or use of an associated principal development; is not required to satisfy minimum requirements of local zoning, subdivision or health regulations; and meets all other non-setback requirements of this Subchapter.

(b) Where application of the oceanfront setback requirements of Rule .0306(a) of this Subchapter would preclude placement of permanent substantial structures on lots existing as of June 1, 1979, single family residential structures shall be permitted seaward of the applicable setback line in ocean erodible areas, but not inlet hazard areas, if each of the following conditions are met:

- (1) The development is set back from the ocean the maximum feasible distance possible on the existing lot and the development is designed to minimize encroachment into the setback area;
- (2) The development is at least 60 feet landward of the vegetation line;
- (3) The development is not located on or in front of a frontal dune, but is entirely behind the landward toe of the frontal dune;
- (4) The development incorporates each of the following design standards, which are in addition to those required by Rule .0308(d) of this Subchapter.
 - (A) All pilings shall have a tip penetration that extends to at least four feet below mean sea level;
 - (B) The footprint of the structure shall be no more than 1,000 square feet or 10 percent of the lot size, whichever is greater.
 - (C) Driveways and parking areas shall be constructed of clay, packed sand or gravel except in those cases where the development does not abut the ocean and is located landward of a paved public street or highway currently in use. In those cases concrete, asphalt or turfstone may also be used.
- (5) All other provisions of this Subchapter and other state and local regulations are met. If the development is to be serviced by an on-site waste disposal system, a copy of a valid permit for such a system shall be submitted as part of the CAMA permit application.

(c) Reconfiguration of lots and projects that have a grandfather status under Paragraph (b) of this Rule shall be allowed provided that the following conditions are met:

- (1) Development is setback from the first line of stable natural vegetation a distance no less than that required by the applicable exception;
- (2) Reconfiguration shall not result in an increase in the number of buildable lots within the Ocean Hazard AEC or have other adverse environmental consequences; and
- (3) Development on lots qualifying for the exception in Paragraph (b) of this Rule shall meet the requirements of Paragraphs (1) through (5) of that Paragraph.

For the purposes of this Rule, an existing lot is a lot or tract of land which, as of June 1, 1979, is specifically described in a recorded plat and which cannot be enlarged by combining the lot or tract of land with a contiguous lot(s) or tract(s) of land under the same ownership. The footprint is defined as the greatest exterior dimensions of the structure, including covered decks, porches, and stairways, when extended to ground level.

(d) The following types of water dependent development shall be permitted seaward of the oceanfront setback requirements of Rule .0306(a) of this Section if all other provisions of this Subchapter and other state and local regulations are met:

- (1) piers providing public access (excluding any pier house, office, or other enclosed areas); and
- (2) maintenance and replacement of existing state-owned bridges and causeways and accessways to such bridges.

(e) Where application of the oceanfront setback requirements of Rule .0306(a) of this Section would preclude replacement of a pier house associated with an existing ocean pier, replacement of the pier house shall be permitted if each of the following conditions are met:

- (1) The associated ocean pier provides public access for fishing or other recreational purposes whether on a commercial, public, or nonprofit basis;
- (2) The pier house is set back from the ocean the maximum feasible distance while maintaining existing parking and sewage treatment facilities and is designed to reduce encroachment into the setback area;
- (3) The pier house shall not be enlarged beyond its original dimensions as of January 1, 1996;
- (4) The pier house shall be rebuilt to comply with all other provisions of this Subchapter; and
- (5) If the associated pier has been destroyed or rendered unusable, replacement of the pier house shall be permitted only if the pier is also being replaced and returned to its original function.

(f) In addition to the development authorized under Paragraph (d) of this Rule, small scale, non-essential development that does not induce further growth in the Ocean Hazard Area, such as the construction of single family piers and small scale erosion control measures that do not interfere with natural ocean front processes, shall be permitted on those non-oceanfront portions of shoreline that exhibit features characteristic of Estuarine Shoreline. Such features include the presence of wetland vegetation, lower wave energy and lower erosion rates than in the adjoining Ocean Erodible Area. Such development shall be permitted under the standards set out in Rule .0208 of this Subchapter. For the purpose of this Rule, small scale is defined as those projects which are eligible for authorization under 15A NCAC 07H .1100, .1200 and 07K .0203.

History Note: Authority G.S. 113A-107(a); 113A-107(b); 113A-113(b)(6)a; 113A-113(b)(6)b; 113A-113(b)(6)d; 113A-124; Eff. February 2, 1981; Amended Eff. February 1, 2006; September 17, 2002 pursuant to S.L. 2002-116; August 1, 2000; August 1, 1998; April 1, 1996; April 1, 1995; February 1, 1993; January 1, 1991; April 1, 1987.

15A NCAC 07H .0310 USE STANDARDS FOR INLET HAZARD AREAS

(a) Inlet areas as defined by Rule .0304 of this Section are subject to inlet migration, rapid and severe changes in watercourses, flooding and strong tides. Due to this extremely hazardous nature of the Inlet Hazard Areas, all development within these areas shall be permitted in accordance with the following standards:

- (1) All development in the inlet hazard area shall be set back from the first line of stable natural vegetation a distance equal to the setback required in the adjacent ocean hazard area;
- (2) Permanent structures shall be permitted at a density of no more than one commercial or residential unit per 15,000 square feet of land area on lots subdivided or created after July 23, 1981;
- (3) Only residential structures of four units or less or non-residential structures of less than 5,000 square feet total floor area shall be allowed within the inlet hazard area, except that access roads to those areas and maintenance and replacement of existing bridges shall be allowed;
- (4) Established common-law and statutory public rights of access to the public trust lands and waters in Inlet Hazard Areas shall not be eliminated or restricted. Development shall not encroach upon public accessways nor shall it limit the intended use of the accessways;
- (5) All other rules in this Subchapter pertaining to development in the ocean hazard areas shall be applied to development within the Inlet Hazard Areas.

(b) The inlet hazard area setback requirements shall not apply to the types of development exempted from the ocean setback rules in 15A NCAC 7H .0309(a), nor, to the types of development listed in 15A NCAC 7H .0309(c).

(c) In addition to the types of development excepted under Rule .0309 of this Section, small scale, non-essential development that does not induce further growth in the Inlet Hazard Area, such as the construction of single-family piers and small scale erosion control measures that do not interfere with natural inlet movement, may be permitted on those portions of shoreline within a designated Inlet Hazard Area that exhibit features characteristic of Estuarine Shoreline. Such features include the presence of wetland vegetation, lower wave energy, and lower erosion rates than in the adjoining Ocean Erodible Area. Such development shall be permitted under the standards set out in Rule .0208 of this Subchapter. For the purpose of this Rule, small scale is defined as those projects which are eligible for authorization under 15A NCAC 7H .1100, .1200 and 7K .0203.

History Note: Filed as a Temporary Amendment Eff. October 30, 1981, for a period of 70 days to expire on January 8, 1982; Filed as an Emergency Rule Eff. September 11, 1981, for a period of 120 days to expire on January 8, 1982;

Authority G.S. 113A-107; 113A-113(b); 113A-124;
Eff. December 1, 1981;
Amended Eff. April 1, 1999; April 1, 1996; December 1, 1992; December 1, 1991;
March 1, 1988.

15A NCAC 07H .0311 INSTALLATION AND MAINTENANCE OF SAND FENCING

- (a) Sand fencing may only be installed for the purpose of building sand dunes by trapping wind blown sand; the protection of the dune(s) and vegetation (planted or existing).
- (b) Sand fencing shall not impede existing public access to the beach, recreational use of the beach, or emergency vehicle access. Sand fencing shall not be installed in a manner that impedes or restricts established common law and statutory rights of public access and use of public trust lands and waters.
- (c) Sand fencing shall not be installed in a manner that impedes, traps or otherwise endangers sea turtles, sea turtle nests or sea turtle hatchlings. CAMA permit applications for sand fencing shall be subject to review by the Wildlife Resources Commission and the U.S. Fish and Wildlife Service in order to determine whether or not the proposed design or installation will have an adverse impact on sea turtles or other threatened or endangered species.
- (d) Non-functioning, damaged, or unsecured sand fencing shall be immediately removed by the property owner.
- (e) Sand fencing shall not be placed on the wet sand beach area.

History Note: Authority G.S. 113A-107; 113A-113(b)(6);
Eff. August 1, 2002.

15A NCAC 07H .0312 TECHNICAL STANDARDS FOR BEACH FILL PROJECTS

Emplacement of sediment along the oceanfront shoreline shall be referred to in this Rule as beach fill. Beach fill projects including beach nourishment, dredged material disposal, habitat restoration, storm protection, and erosion control may be permitted under the following conditions:

- (1) The applicant shall characterize the recipient beach according to the following methodology:
 - (a) Characterization of the recipient beach shall not be required for the placement of sediment directly from and completely confined to a federally or state maintained navigation channel;
 - (b) Sediment sampling and analysis shall be used to capture the three-dimensional spatial variability of the sediment characteristics including grain size, sorting and mineralogy within the natural system;
 - (c) Shore-perpendicular topographic and bathymetric surveying of the recipient beach shall be conducted to determine the beach profile. Topographic and bathymetric surveying shall occur along a minimum of five (5) shore-perpendicular transects evenly spaced throughout the entire project area. Each transect shall extend from the frontal dune crest seaward to a depth of 20 feet (6.1 meters) or to the shore-perpendicular distance 2,400 feet (732 meters) seaward of mean low water, whichever is in a more landward position. Transect spacing shall not exceed 5,000 feet (1,524 meters) in the shore-parallel direction. Elevation data for all transects shall be referenced to the North American Vertical Datum on 1988 (NAVD 88) and the North American Datum of 1983 (NAD 83);
 - (d) No less than 13 sediment samples shall be taken along each beach profile transect. At least one (1) sample shall be taken from each of the following morphodynamic zones where present: frontal dune, frontal dune toe, mid berm, mean high water (MHW), mid tide (MT), mean low water (MLW), trough, bar crest and at even depth increments from 6 feet (1.8 meters) to 20 feet (6.1 meters) or to a shore-perpendicular distance 2,400 feet (732 meters) seaward of mean low water, whichever is in a more landward position. The total number of samples taken landward of MLW shall equal the total number of samples taken seaward of MLW;
 - (e) For the purpose of this Rule, sediment grain size categories shall be defined as “fine” (less than 0.0625 millimeters), “sand” (greater than or equal to 0.0625 millimeters and less than 2 millimeters), “granular” (greater than or equal to 2 millimeters and less than 4.76 millimeters) and “gravel” (greater than or equal to 4.76 millimeters and less than 76 millimeters). Each sediment sample shall report percentage by weight of each of these four (4) grain size categories;
 - (f) A composite of the simple arithmetic mean for each of the four (4) grain size categories defined in Sub-Item (1)(e) of this Rule shall be calculated for each transect. A grand mean shall be established for each of the four (4) grain size categories by summing the mean for each transect and dividing by the total number of transects. The value that characterizes grain size values for the recipient beach shall be the grand mean of percentage by weight for each grain size category defined in Sub-Item (1)(e) of this Rule;
 - (g) Percentage by weight calcium carbonate shall be calculated from a composite of all sediment samples along each transect defined in Sub-Item (1)(d) of this Rule. The value that characterizes

- the carbonate content of the recipient beach shall be a grand mean calculated by summing the percentage by weight calcium carbonate for each transect and dividing by the total number of transects. For beaches on which fill activities have taken place prior to the effective date of this Rule, the Division of Coastal Management shall consider visual estimates of shell content as a proxy for carbonate weight percent;
- (h) The total number of sediments and shell material greater than three (3) inches (76 millimeters) in diameter, observable on the surface of the beach between mean low water (MLW) and the frontal dune toe, shall be calculated for an area of 50,000 square feet (4,645 square meters) within the beach fill project boundaries. This area shall be considered a representative sample of the entire project area and referred to as the “background” value;
 - (i) Beaches that have received sediment prior to the effective date of this Rule shall be characterized in a way that is consistent with Sub-Items (1)(a) through (1)(h) of this Rule and shall use data collected from the recipient beach prior to the addition of beach fill. If such data were not collected or are unavailable, a dataset best reflecting the sediment characteristics of the recipient beach prior to beach fill shall be developed in coordination with the Division of Coastal Management and;
 - (j) All data used to characterize the recipient beach shall be provided in digital and hardcopy format to the Division of Coastal Management upon request.
- (2) The applicant shall characterize the sediment to be placed on the recipient beach according to the following methodology:
- (a) The characterization of borrow areas including submarine sites, upland sites, and dredged material disposal area shall be designed to capture the three-dimensional spatial variability of the sediment characteristics including grain size, sorting and mineralogy within the natural system or dredged material disposal area;
 - (b) The characterization of borrow sites shall include sediment characterization data provided by the Division of Coastal Management;
 - (c) Seafloor surveys shall measure elevation and provide acoustic imagery of the seafloor. Measurement of seafloor elevation at each submarine borrow site shall provide 100 percent coverage and use survey-grade swath sonar in accordance with current US Army Corps of Engineers standards for navigation and dredging. Seafloor imaging without an elevation component shall also provide 100 percent US Army Corps of Engineers standards for navigation and dredging. Because shallow submarine areas can provide technical challenges and physical limitations for acoustic measurements, alternative elevation surveying methods for water depths less than 10 feet (3 meters) may be evaluated on a case-by-case basis by the Division of Coastal Management and seafloor imaging without an elevation component may not be required for water depths less than 10 feet (3 meters). Elevation data shall be tide- and motion-corrected and referenced to the North American Vertical Datum of 1988 (NAVD 88) and the North American Datum of 1983 (NAD 83). Seafloor imaging data without an elevation component shall be referenced to the NAD 83. All final seafloor survey data shall conform to standards for accuracy, quality control and quality assurance as set forth either by the US Army Corps of Engineers, the National Oceanic and Atmospheric Administration, or the International Hydrographic Organization;
 - (d) Geophysical imaging of the seafloor subsurface shall be used to characterize each borrow site and shall use survey grids with a line spacing not to exceed 1,000 feet (305 meters). Survey grids shall incorporate at least one (1) tie point per survey line. Because shallow submarine areas can pose technical challenges and physical limitations for geophysical techniques, subsurface data may not be required in water depths less than 10 feet (3 meters). Subsurface geophysical imaging shall not be required for federally or state maintained navigation channels or upland sites. All final subsurface geophysical data shall use accurate sediment velocity models for time-depth conversions and be referenced to the North American Datum of 1983 (NAD 83);
 - (e) Sediment sampling of all borrow sites shall use a vertical sampling device no less than 3 inches (76 millimeters) in diameter. Characterization of each borrow site shall use no less than 10 evenly spaced cores or one (1) core per 23 acres (grid spacing of 1,000 feet or 305 meters), whichever is greater. Characterization of borrow sites completely confined to federally or state maintained navigation channels shall use no less than five (5) evenly spaced vertical samples per channel or sample spacing of no more than 5,000 linear feet (1,524 meters), whichever is greater. In submarine borrow sites other than federally or state maintained navigation channels where water depths are no greater than 10 feet (3 meters) geophysical data of and below the seafloor are not acquired, sediment sample spacing shall be no less than one (1) core per six (6) acres (grid spacing of 500 feet or 152 meters). Vertical sampling shall penetrate to a depth equal to or greater than permitted dredge or excavation depth or expected dredge or excavation depths for pending

- permit applications. All sediment samples shall be integrated with geophysical data to constrain the surficial, horizontal and vertical extent of lithologic units and determine excavation volumes of compatible sediment as defined in Item (3) of this Rule;
- (f) Grain size distributions shall be reported for all sub-samples taken within each vertical sample for each of the four (4) grain size categories defined in Sub-Item (1)(e) of this Rule. Weighted averages for each core shall be calculated based on the total number of samples and the thickness of each sampled interval. A simple arithmetic mean of the weighted averages for each grain size category shall be calculated to represent the average grain size values for each borrow site. Vertical samples shall be geo-referenced and digitally imaged using scaled, color-calibrated photography; and
 - (g) Percentage by weight of calcium carbonate shall be calculated from a composite sample of each core. A weighted average of calcium carbonate percentage by weight shall be calculated for each borrow site based on the composite sample thickness of each core. Carbonate analysis shall not be required for sediment confined to federally or state maintained navigation channels; and
 - (h) All data used to characterize the borrow site shall be provided in digital and hardcopy format to the Division of Coastal Management upon request.
- (3) The Division of Coastal Management shall determine sediment compatibility according to the following criteria:
- (a) Sediment completely confined to the permitted dredge depth of a federally or state maintained navigation channel shall be considered compatible if the average percentage by weight of fine-grained (less than 0.0625 millimeters) sediment is less than 10 percent;
 - (b) Sediment used solely to establish or strengthen dunes shall not be considered a beach fill project under this Rule;
 - (c) Sediment used solely to re-establish state-maintained transportation corridors across a barrier island breach in a disaster area as declared by the Governor shall not be considered a beach fill project under this Rule;
 - (d) The average percentage by weight of fine-grained sediment (less than 0.0625 millimeters) in each borrow site shall not exceed the average percentage by weight of fine-grained sediment of the recipient beach characterization plus five (5) percent;
 - (e) The average percentage by weight of granular sediment (greater than or equal to 2 millimeters and <less than 4.76 millimeters) in a borrow site shall not exceed the average percentage by weight of coarse-sand sediment of the recipient beach characterization plus five (5) percent;
 - (f) The average percentage by weight of gravel (greater than or equal to 4.76 millimeters) in a borrow site shall not exceed the average percentage by weight of gravel-sized sediment for the recipient beach characterization plus five (5) percent;
 - (g) The average percentage by weight of calcium carbonate in a borrow site shall not exceed the average percentage by weight of calcium carbonate of the recipient beach characterization plus 15 percent; and
 - (h) Techniques that take incompatible sediment within a borrow site or combination of sites and make it compatible with that of the recipient beach characterization shall be evaluated on a case-by-case basis by the Division of Coastal Management.
- (4) Excavation and placement of sediment shall conform to the following criteria:
- (a) Sediment excavation depth from a federally or state maintained navigation channel shall not exceed the permitted dredge depth of the channel;
 - (b) Sediment excavation depths for all borrow sites shall not exceed the maximum depth of recovered core at each coring location;
 - (c) In order to protect threatened and endangered species, and to minimize impacts to fish, shellfish and wildlife resources, no excavation or placement of sediment shall occur within the project area during times designated by the Division of Coastal Management in consultation with other State and Federal agencies, and;
 - (d) Sediment and shell material with a diameter greater than three (3) inches (76 millimeters) shall be considered incompatible if it has been placed on the beach during the beach fill project, is observed between mean low water (MLW) and the frontal dune toe, and is in excess of twice the background value of material of the same size along any 50,000-square-foot (4,645 square meter) section of beach.

History Note: Authority G.S. 113-229; 113A-102(b)(1); 113-229; 113A-103(5)(a); 113A-107(a); 113A-113(b)(5) and (6); 113A-118; 113A-124;
 Eff. February 1, 2007;
 Amended Eff. April 1, 2008.

